

Product cards and safety instructions for BAM pressure gauges include three specialized models of diagnostic blood pressure monitors: PPM001, PPM002 and PPM045. These devices are designed to precisely measure tire pressure in passenger cars, vans, and trucks.

PRODUCT CARDS

BAM PPM001: Flexible wheel pressure gauge 16 BAR (hose + extension)

- **Application:** Measuring tire pressure in passenger cars and delivery vans.
- **Measuring range:** 0 – 16 BAR.
- **Cable construction:** Flexible, bendable hose with additional extension.
- **Identification:** EAN code 5902315128668

BAM PPM002: Flexible tire pressure gauge 12 BAR (hose)

- **Application:** Standard pressure diagnostics in passenger cars.
- **Measuring range:** 0 – 12 BAR.
- **Cable construction:** Flexible, durable measuring hose.
- **Identification:** EAN code 5902315124455.

BAM PPM045: Rigid pressure gauge for truck wheels 15 BAR (metal)

- **Application:** Professional measurement in trucks and machines.
- **Measuring range:** 0 – 15 BAR.
- **Design:** Completely metal, resistant to workshop conditions.
- **Tip type:** Rigid construction for easy access to twin valves.

GENERAL SAFETY INSTRUCTIONS (GIS)

1. General rules

- Use only as intended for compressed air.
- The maximum operating pressure (12, 15 or 16 BAR, respectively) must not be exceeded.
- Protect the indicator dial from strong impacts and falls.

2. Safety during measurement

- Wear safety glasses to protect against debris and air blasts.
- Before measuring, check the technical condition of the hose or rigid tip.
- Press the tip perpendicular to the valve to avoid side air ejection.

3. Maintenance and storage

- Store in a dry place away from grease and oils.
- Do not expose the device to direct exposure to extreme temperatures.
- If the glass or body cracks, remove from service immediately.